

Spray Nozzle Series

Leak Lock Type

Special design for avoiding oil leaking. Not delaying spraying fluid which prolongs the longevity of the tool holders. Slope angle: $\pm 35^\circ$. The angle is easy to adjust by hand. Easy operation and greatest stability when operating. We have Multiple sizes for your reference. Customer requested sizes are available. Leak lock spray nozzle is made by stainless steel. It extends the lifetime of the tools and avoids corrosion. Moreover, it is accordance with RoHS standard and passed SGS certification which avoids polluting the environment. We have self-made testing equipment and QC before delivery. With our quality assurance, you can have confidence in us.

噴水頭系列 止漏型

特殊設計可立即停止供給切削液，將不再有切削油滴漏的困擾。且出水不延遲，可延長刀具使用壽命。傾斜角度： $\pm 35^\circ$ ，以手即輕易調整至您希望的角度，容易操作使用且穩定性佳。規格齊全供您選擇，並可依客戶需求訂作。亦有不銹鋼材質的噴水頭，可延長產品壽命，防止生銹。且通過 SGS 認證，符合 RoHS 標準，不污染環境。擁有自製的檢驗設備，出貨前一律全檢，讓您對品質更安心。



Alloy Steel Type 合金鋼型

Code No. 型號	Thread mount 螺紋組接	L	L1	D1	D2	d	H
9017500	PT 1/8	40	10	6	6	4	17
9017600	PT 1/8	60					
9017700	PT 1/4	40					
9017800	PT 1/4	60	13	8	10	6	24
9017900	PT 3/8	30					
9018000	PT 3/8	50					
9018100	PT 3/8	70	10	6	6	4	17
9018500	NPT 1/4	40					
9018600	NPT 1/4	60					
9018700	NPT 3/8	30	13	8	10	6	24
9018800	NPT 3/8	50					
9018900	NPT 3/8	70					
9019000	M10*1.25P	40	10	6	6	4	17
9019100	M10*1.25P	60					
9019200	M20*1.5P	30	13	8	10	6	24
9019300	M20*1.5P	50					
9019400	M20*1.5P	70					

Stainless Type 不銹鋼型

Code No. 型號	Thread mount 螺紋組接	L	L1	D1	D2	d	H
9017510	PT 1/8	40	10	6	6	4	17
9017610	PT 1/8	60					
9017710	PT 1/4	40					
9017810	PT 1/4	60	13	8	10	6	24
9017910	PT 3/8	30					
9018010	PT 3/8	50					
9018110	PT 3/8	70	10	6	6	4	17
9018510	NPT 1/4	40					
9018610	NPT 1/4	60					
9018710	NPT 3/8	30	13	8	10	6	24
9018810	NPT 3/8	50					
9018910	NPT 3/8	70					
9019010	M10*1.25P	40	10	6	6	4	17
9019110	M10*1.25P	60					
9019210	M20*1.5P	30	13	8	10	6	24
9019310	M20*1.5P	50					
9019410	M20*1.5P	70					